

# NT78



15.7×12.3×14

UL E160644 CQC 03001003504

Features
<ul style="list-style-type: none"> <li>Small size, lightweight.</li> <li>Low coil consumption.</li> <li>PC board mounting.</li> <li>Suitable for household electrical appliances, automation system, electronic equipment, instrument, meter, telecommunication facilities and remote control facilities.</li> </ul>

Ordering Information
<b>NT78 C S 10 DC12V 0.6</b> 1 2 3 4 5 6
1 Part number: NT78 2 Contact arrangement: A:1A; B:1B; C:1C; U:1U 3 Enclosure: S: Sealed type; NIL: Dust cover 4 Contact rating: 10A,20A,30A/14VDC; 10A/120VAC; 5A/250VAC 5 Coil rated voltage(V): DC:6,9,12,24 6 Coil power consumption: 0.6:0.6W; 0.8:0.8W

Contact Data		1A (SPSTNO) 1B (SPSTNC) 1C (SPDT(B-M)) 1U (SPSTNODM)	
Contact Arrangement		AgCdO AgSnO <sub>2</sub>	
Contact Material		NO:20A/14VDC 10A/120VAC,5A/250VAC NC:15A/14VDC,10A/120VAC,5A/250VAC IA:30A/14VDC IU:2×10A/14VDC Motor load : 1/2HP 125VAC Lamp load : TV-5	
Contact Rating (resistive)		420W 1250VA	
Max. Switching Power		42VDC 380VAC Max. Switching Current:30A	
Max. Switching Voltage		≤50mΩ Item 4.12 of IEC 61810-7	
Contact Resistance or Voltage drop		10 <sup>5</sup> Item 4.30 of IEC 61810-7	
Operational life	Electrical	10 <sup>7</sup> Item 4.31 of IEC 61810-7	
	Mechanical	10 <sup>7</sup> Item 4.31 of IEC 61810-7	

CAUTION: 1.For the intermediate current, it only applies to the room temperature.

Dash numbers	Coil voltage VDC		Coil resistance Ω ±10%	Pickup voltage VDC(max) (80% of rated voltage)	Release voltage VDC(min) (5% of rated voltage)	Coil power consumption W	Operate Time ms	Release Time ms
	Rated	Max.						
006-600	6	6.6	60	4.8	0.30	0.6	≤10	≤5
009-600	9	9.9	135	7.2	0.45			
012-600	12	13.2	240	9.6	0.60			
024-600	24	26.4	960	19.2	1.20			
006-800	6	6.6	45	4.8	0.30	0.8	≤10	≤5
009-800	9	9.9	102	7.2	0.45			
012-800	12	13.2	180	9.6	0.60			
024-800	24	26.4	720	19.2	1.20			

CAUTION: 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.  
2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.

Operation condition		
Insulation Resistance	100MΩ min (at 500VDC)	Item 7 of IEC 60255-5
Dielectric Strength	Between contacts	50Hz 500V
	Between contact and coil	50Hz 500V
Shock resistance	100m/s <sup>2</sup> 11ms	IEC68-2-27 Test Ea
Vibration resistance	10Hz~55Hz double amplitude 1.5mm	IEC68-2-6 Test Fc
Terminals strength	10N	IEC68-2-21 Test Ua1
Solderability	235°C ±2°C 3s±0.5s	IEC68-2-20 Test Ta method 1
Ambient Temperature	-40°C~85°C	
Relative Humidity	85% (at 20°C)	IEC68-2-3 Test Ca
Mass	6g	

Safety approval	UL&CUR	CQC
Load	NO: 20A/14VDC 10A/120VAC NC: 10A/14VDC 1/2HP 125VAC TV-5	5A/250VAC

### Dimensions

mm / inch

### Dimensions

15.7Max. 0.618max.  
12.3Max. 0.484max.  
1.4Max. 0.551max.  
3.5 0.138  
0.4 0.016  
1.45 0.057  
5-1.1X0.4 0.043×0.016  
5 0.197 0.0197  
5-∅1.4 ∅0.055  
2.5 0.098  
10.2 0.401

### Mounting (Bottom view)

### Wiring diagram (Bottom view)

1C 1B 1A 1U

NOTES 1).Dimensions are in millimeters.  
2).Inch equivalents are given for general information only.

