



Main Feature:

- Socket with screw terminal.
- No reduction of protection class or creepage/clearance with plastic retainer.
- Easy replacement of relays on a densely packed DIN rail.
- Retainer clip with ejection function for relays of 29 or 35mm height.
- Socket can be used as connector for diagnosis function.
- Sockets and accessories: RoHS compliance (Directive 2002/95/EC).

Socket with screw-type terminal for DIN-rail mounting
Approvals:



E306487

Accessories:


LED Module:




Grip:



Jump Link:



Writing Tab:



Technical data:

Rated current	12A
Rated voltage / max. Switching voltage AC	150/300 VAC
Dielectric strength coil-contact circuit	2,500 V _{rms}
Clearance / creepage coil-contact circuit	≥ 3/4mm
Material group of insulation parts	≥ IIIa
Insulation to IEC 60664-1	
Type of insulation coil-contact circuit	basic
Open contact circuit	functional
Rated insulation voltage	250V
Pollution degree	2
Rated voltage system	230/400V
Over voltage category	III
RoHS Directive 2002/95/EC	
Sockets, retainers and marking tag:	compliant
Degree of protection DIN 40050	IP20
Ambient temperature range	-25...+70°C
Terminals	screw
Terminal screw torque acc. IEC 61984	0.5Nm
Max.	0.7Nm
Wire cross section	
Single wire	1x4.0mm ²
Fine wire	2x2.5mm ²
With bootlace crimp (DIN 46228/1)	2x1.5mm ²
Insertion cycles	A (10)
Max. Insertion Force total	100N
Mounting distance	0, dense packing
Weight	44g
Packaging unit	10 pcs.

Order Information:

CST - S 08 F3 - □

① ② ③ ④ ⑤

①	Item:	CST
②	Contact form:	S (for Screw Type) C (for Cage Clamp Type)
③	Relay terminals:	08 (for 08 Terminals Relay) 11 (for 11 Terminals Relay) 14 (for 14 Terminals Relay)
④	Insulation levels:	F2 (for Two Levels) F3 (for Three Levels)
⑤	Special remark:	Nil (for Standard) T (for Tyco LED Module) H (for High Insulation)

Dimension:

