

Main Feature



1. Small size with slim width.
2. SPST and SPDT Contact forms are available.
3. Contact Capacity is 10A.
4. Surge Strength can be up to 8,000V.
5. Halogen Free series is available.



Contact Rating

Load Type	JQ (DM/TM/LM)	JQ (D/T)
Rated Load (Resistive)	10A 125VAC	NO:10A 125VAC
	5A 250VAC	5A 250VAC
	5A 30VDC	5A 30VDC
	-	NC: 5A 125VAC
	-	3A 250VAC
Rated Carrying Current	5A	5A
Max. Allowable Voltage	AC 250V	AC 250V
	DC 30V	DC 30V
Max. Allowable Current	10A	10A
Max. Allowable Power Force	1,250VA	1,250VA
	150W	150W
Contact Material	Ag Alloy	Ag Alloy
Contact Form	SPST	SPDT

Application

Air Conditioner, Fan Control, Home Appliances, Timer and Thermal Control Application.

Performance (at Initial Value)

- Contact Resistance 100mΩMax. @1A,6VDC
- Operate Time..... 6 mSec. Max.
- Release Time 2 mSec. Max.
- Dielectric Strength :
Between Coil & Contact 4,000VAC at 50/60 Hz for one minute.
Between Contacts 1,000VAC at 50/60 Hz for one minute.
- Surge Strength 8,000V (between coil & contact 1.2x50μSec.)
- Insulation Resistance 100 MegaΩ Min.at 500VDC.
- Max. On/Off Switching :
Electrical..... 6 Cycles per Minute.
Mechanical 300 Cycles per Minute.
- Temperature Range..... -40~70°C.
- Humidity Range..... 45~85% RH

- Coil Temperature Rise 45°C Max.
- Vibration :
Endurance 10 to 55 Hz dual.
amplitude width 1.5mm.
Error Operation..... 10 to 55 Hz dual.
amplitude width 1.5mm.
- Shock :
Endurance 1,000 m/S².
Error Operation..... 100 m/S².
- Life Expectancy :
Mechanical 10⁷ Operations at No Load condition.
Electrical 10⁵ Operations at Rated Resistive Load.
- Weight About 5.6g.

Safety Standard & Its File Number

- UL & C-UL E141060
- TÜV R50008011
- VDE 40010922
- CQC.....07001018734(For D/DM/LM)

Coil Specification (at 20°C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ($\Omega \pm 10\%$)	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
JQ-D/DM	3	150	20	Abt. 0.45	75% Maximum	5% Minimum	120%
	5	91	55				
	6	75	80				
	9	50	180				
	12	37.5	320				
JQ-T/TM	3	133.3	22.5	Abt.0.4	75% Maximum	5% Minimum	120%
	5	80	62.5				
	6	66.7	90				
	9	44.4	202				
	12	33.3	360				
JQ-LM	3	67	45	Abt.0.2	75% Maximum	5% Minimum	120%
	5	40	125				
	6	33.3	180				
	9	22.5	400				
	12	16.7	720				
	24	8.3	2,800				

Ordering Information

JQ - SS - 1 12 D M F

Insulation System:

Nil: Standard Class

F: F Class

Contact Form:

Nil: One Form C (for D, T Type Only)

M: One Form A

Coil Type:

D: Standard DC Coil

T: Middle Consumption DC Coil

L: High Sensitivity DC Coil

Coil Voltage:

03: 3V, 05: 5V, 06: 6V, 09: 9V, 12: 12V, 24: 24V

Number of Pole:

1: One Pole

Type of Sealing:

SS: RT II Flux Proofed Relays

SH: RT III Wash Tight Relays

Type:


JQ

Classification

Model	JQ				
	1C		1A		
Contact Form	1C		1A		
Coil Type	Standard DC Coil	Middle Consumption	Standard DC Coil	Middle Consumption	High Sensitivity DC
Flux Proofed Relay	JQ-SS-1□□D	JQ-SS-1□□T	JQ-SS-1□□DM	JQ-SS-1□□TM	JQ-SS-1□□LM
Wash Tight Relay	JQ-SH-1□□D	JQ-SH-1□□T	JQ-SH-1□□DM	JQ-SH-1□□TM	JQ-SH-1□□LM

Dimension ($\leq 5\text{mm} \pm 0.2\text{mm}$, $> 5\text{mm} \pm 0.3\text{mm}$, the tolerance of PCB thru hole: $+0.1\text{mm}$)

JQ-SS/SH-DM/TM/LM



JQ-SS/SH-D/T

